



The **NCNW-2 Wireless UHF Pull Cord Transmitter** is designed to send a pre-programmed text message directly to a designated pager or LED display.

When the NCNW-2 is reset to its normal position, a cancellation alert can be sent. In addition, the NCNW-2 can generate an automated message to report low battery status. The WPT-02 includes a pull cord and mounting hardware.

***Note:** An extra deep plastic single gang box is required for optimal signal coverage.

Key Features

- **Two Programmable Messages**
- **Sends Message Directly to a Pager**
- **300' - 1,000' Range (Can be Increased by Using a Data Repeater)**
- **Transmission Indicator**
- **In-Wall Mount, Surface Mount Installation Option**
- **Long-life Single Lithium Battery**
- **Low Battery Alert**

Specifications:

Dimensions	2.8" x 4.5" x 2.5" (W x H x D)	Activation Type/Call Cancel	Toggle
Weight	2.6 oz.	Signalling Time	2 - 4 Seconds
Power	Single 3V Lithium Battery	Stability	Better than 5 PPM
Color	White	Frequency	467.8000 MHz (Additional Frequencies Available)
Operating Temperature	32° - 140°F	Paging Format	POCSAG, 512 or 1200 BPS
Humidity	0% - 90%, Non-Condensing	Channel Spacing	12.5 KHz - Narrow Band
RF Power	10 mW	Activation Codes	3 (Call, Cancel & Low Battery)
Programming	PC Based Programming Kit	Limited Warranty	One Year Parts and Labor